

AC/DC POWER SUPPLY- 960W

THREE PHASE DIN RAIL MOUNTING TYPE



Power Supplies

5332x SERIES



MAIN FEATURES:

- 960W Slim Size – 110mm width
- Built-in Active PFC Function
- Regulated Output Range: 24VDC–48VDC
- Input Range: Three-phase 340VAC – 550VAC wide range input
- Current Sharing Function(3+1)
- DC OK Relay Contact
- High Energetic Efficiency: Meets the requirements of Energy Star and EC Code of Conduct
- Operating Altitude:5000 meters
- Safety : Meets All Requirments of UL61010-1, UL61010-2-201,EN/IEC61558-1,EN/IEC61558-2-16, IEC/EN62368-1,UL62368-1,CSA22.2NO.62368-1-14, CE, UKCA
- EMC Emission : conform to EN55032(CISPR 32), EN61204-3, EN/IEC61000-3-2 Class C, EN61000-3-3
- EMC Immunity: conform to EN61000-4-2, EN/IEC61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-11
- Over Voltage Category : OVCIII @ IEC/EN61558-1

DATA SHEET



Part No.	Power Rating Watts	Output Voltage (VDC)	Rated Output Current (A)	Output Voltage Range-ADJ(Vdc)	Ambient Temp. (°C)	Efficiency Typical	Input Range
53323	960	24	40	24 ~ 28	-30°C ~ +70°C	94%	Three-Phase 340 ~ 550VAC Or (480-780VDC)
53324	960	36	26.6	36 ~ 42	-30°C ~ +70°C	94%	
53325	960	48	20	48 ~ 55	-30°C ~ +70°C	94%	

NOTE : Other output voltage are available upon request.

Please refer to MYRRA's website and catalogue for MYRRA SMPS application notes.

The information contained in this document is subject to change without notice.

www.myrra.com
www.myrra-powersupplies.com
contact us : contact@myrra.com

AC/DC POWER SUPPLY- 960W

THREE PHASE DIN RAIL MOUNTING TYPE



5332x SERIES

Power Supplies

Model : 960 Watt		Specifications
AC Input Characteristics	Rated Input Voltage	Three-phase 380~500VAC or 540VDC-710VDC (Dual phase operation possible in connecting L1,L3,FG or L2,L3,FG)
	Input Voltage Range	Three-phase 340~550VAC or 480VDC-780VDC (Dual phase operation possible in connecting L1,L3,FG or L2,L3,FG)
	AC Input Frequency Range	47Hz~63Hz
	Rated AC Input Frequency	50/60Hz
	Input Current	2.5A Max.
	Input Inrush Current	60A @ cold start
	Power Factor	>0.88@400Vac input at full load >0.86@500Vac input at full load
	Leakage Current	< 3.5mA/530VAC
DC Output Characteristics	Output Voltage Accuracy	±1% (Output Voltage ADJ Range See table)
	Output Voltage Line Regulation	± 0.5%
	Output Voltage Load Regulation	± 1%
	Ripple & Noise	Max. 200mVp-p@ Rated AC input, at nominal line (The measuring will be terminated with a 47µF AL E-Cap and a 0.1µF Ceramic-Cap. An oscilloscope set at 20MHz bandwidth)
	Dynamic Response	The output voltage shall not exceed ± 10% rated output voltage @ 50% ~ 90 % Load change, 1A/µS, 1KHz 50% duty cycle
	Hold Up Time	10mS typ.@ 400VAC, 12mS typ.@500Vac at full load
	Turn On Delay	2S max. @ 340VAC~550VAC input and DC output with full load
	Rise Time	110ms max. @ 400VAC , 100ms max.@500Vac at full load
	Overshoot	The output voltage shall not exceed +10% rated output voltage @ Power on and 340VAC~550VAC input, and DC with full load
	Undershoot	The output voltage shall not exceed -10% rated output voltage @ Power off and 340VAC~550VAC input and DC output with full load

The information contained in this document is subject to change without notice.

Please refer to MYRRA's website and catalogue for MYRRA SMPS application notes.

www.myrra.com

www.myrra-powersupplies.com

contact us : contact@myrra.com

AC/DC POWER SUPPLY- 960W

THREE PHASE DIN RAIL MOUNTING TYPE



5332x SERIES

Power Supplies

	Efficiency	See table (Meets the requirements of Energy Star and the EC Code of Conduct)
Protection Characteristics	Over Current Protection	The power supply shall automatic protection @ 105% ~140% rated output power. Protection type : Constant current limiting, unit will shut down after 3 sec. ,re-power on to recover. No excessive heat, odour, no safety hazard
	Output Short Circuit Protection	The power supply shall withstand a continuous output short without damage in 24 hours; The short may be applied before power on, or after power on; The power supply shall resume normal operation after the short is removed, no excessive heat, odour ,no safety hazard.
	Over temperature protection	The power supply is built thermal protection function and can be shut down(hiccup mode) when NTC thermistor's body temperature reach approx.110°C@ power supply operating ambient temperature apprxo.+65°C ±10°C @ at the DC output with full load. The power supply shall auto-recovery normal operation,it is subject to the shut-down is long enough to allow the thermal detection is down to auto reset.
	Over voltage protection	Production type: shut down output voltage and re-power on to recover.
	Current Sharing Function	Current sharing
DC OK Function	DC OK Relay Contact Rantings	60Vdc/0.3A; 30Vdc/1A; 30Vac/0.5A resistive load
Environmental	Operation Temperature	-30°C~+70°C (Refer to« DERATING GRAPH »)
	Operation Humidity	20~95% RH (No Condensing) @ full load
	Storage Temperature	-40°C~ +85°C (Recommended +5°C~ +35°C)
	Storage Humidity	10%~95% (Recommended <75%RH)
	Cooling Method	Ordinary or thermostat
	Operation Altitude	5000 meters The ambient temperature derating of 3.5°C/1000m with fanless models and of 5°C/1000m with fan models for operating altitude higher than 2000m(6500ft)
	Dielectric Strength	Input to Output : 3000VAC 5mA, 3 sec. Input to FG: 2000VAC 10mA, 3 sec. Output to FG: 500VAC 10mA, 3 sec Output to DC OK: 500VAC 10mA, 3 sec

AC/DC POWER SUPPLY- 960W

THREE PHASE DIN RAIL MOUNTING TYPE



Safety & EMC Requirement	Insulation Resistance	100MΩ max @500Vdc/25°C/70% RH
	Radiation	Meets EN55032(CISPR32), EN/IEC61204-3, Class B. under 3dB margin
	Conduction	Meets EN55032(CISPR32), EN/IEC61204-3, Class B. under 3dB margin
	Harmonic Current Distance	Meets EN/IEC61000-3-2, Class C
	Voltage Fluctuation and Flicker	Meets EN61000-3-3
	Electrostatic Discharge	Meets EN61000-4-2 Contact Discharge ± 8KV, Air Discharges ± 15KV
	RF Field Strength Susceptibility	Meets EN/IEC61000-4-3
	Electrical Fast Transient	Meets EN61000-4-4, ± 4KV
	Lightning Surge	Meets EN61000-4-5, ±4KV common mode,±2KV diff.mode
	Conducted Susceptibility	Meets EN61000-4-6
Safety & EMC Requirements	Power Frequency Magnetic Field Susceptibility Test	Meeting EN61000-4-8
	Voltage Dips and interruptions	Meets EN61000-4-11 >95% dip 0.5 periods, 30% dip 25 periods 95% interruptions 250 periods
	Safety Standards	Meets all requirements of : UL61010-1,UL61010-2-201 UL62368-1, CSA22.2No.62368-1-14 IEC/EN62368-1 IEC/EN61558-1 IEC/EN61558-2-16 CE,UKCA
Reliability Requirement	MTBF	>200K Hours @400VAC input at +25deg.C Calculated in accordance with MIL-HDBK-217-F2
	Burn-in-Test	The unit shall be burned in 2~5hours and DC with full load at and ambient temperature of 30~45 degrees C
Mechanical	Physical size	The units dimension is : (L)150*(W)125.5*(H)110mm (±1mm) (see appearance drawing)
	Net Weight	Approximately 2450 grams per product unit
Guarantee	This product is in accordance with the European RoHS & REACH directives	


AC/DC POWER SUPPLY- 960W

THREE PHASE DIN RAIL MOUNTING TYPE





Power Supplies

BLOCK DIAGRAM



DERATING GRAPH



Current Sharing

The output voltage difference of each single module is less than or equal to 100mV, and a better comprehensive effect of line terminal output voltage and current sharing can be obtained;

The output voltage of each power module will affect the current sharing accuracy. The output voltage of the power module is rated voltage $\pm 100\text{mV}$. In practical applications, if the output voltage value needs to be adjusted, the output voltages of all parallel power modules need to be adjusted to the same voltage. The recommended voltage range is: target voltage value $\pm 100\text{mV}$.

After the output load of each power module is greater than 50% of the rated load, the current sharing accuracy is required to be $\pm 5\%$.

Note:

1. When used in parallel, the number of parallel modules cannot exceed 4.
2. When the power modules work in parallel, there is an active current sharing circuit inside to ensure that the current between each module remains balanced


AC/DC POWER SUPPLY- 960W

THREE PHASE DIN RAIL MOUNTING TYPE




Power Supplies

DIMENSIONS



INSTALLATION INSTRUCTION



Admissible Din-Rail: TS35/7.5 or TS35/15, For reference only, not included with unit.